

#### **GENERAL**

Sink bowl seamlessly drawn of heavy gauge, nickel bearing stainless steel. Self-rimming.

## **DESIGN FEATURES**

Bowl Depth: 5-1/8".

Coved Corners: Interior vertical and horizontal corners are rounded to a minimum of 2-1/4" radii.

Finish: Exposed surfaces are polished to a satin finish with highshine bowl radius.

Underside: Undercoated as described below.

Self-rimming: Sink is furnished with appropriate number of clips and screws to provide a secure installation.

### OTHER

Drain Opening: 2" (D11515 and D611515), 3-1/2" (D11516).

NOTE: Unless otherwise specified, sink is furnished with 2 faucet holes.

This sink complies with ANSI Standard A112.19.3M.



This sink is listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.


# **SINK DIMENSIONS (INCHES)\***

Model	Overall		Inside Bowl			Cutout in Countertop 11/2" Radius Corners		No. of 1¹/4" Dia. Faucet Holes	Minimum Cabinet	Ship. Wt.
Number	L	W	L	W	D	L	W	4" Center	Size	Lbs.
D11515	15	15	12	10	51/8	143/8	143/8	1, 2 or 3	18	41/2
D11516	15	15	12	10	51/8	143/8	143/8	1, 2 or 3	18	5
D611515	15	15	12	10	51/8	143/8	143/8	1 or 2	18	20

<sup>\*</sup>Length is left to right. Width is front to back.

D-Prefix sinks are packed one per shipping carton. Sink bowl is fully undercoated to prevent condensation and deaden sound.

D6-Prefix sinks are nested 6 units per shipping carton. Sink bowls are sound deadened on bottom only.



Bowl Depth is 5-1/8" Model D115152 Illustrated

Model D115152

ALL DIMENSIONS IN INCHES, TO CONVERT TO MILLIMETERS MULTIPLY BY 25.4.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice.

This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

2-3F